

SYNTHETIC UNDERLAYMENT

Product Specification			Test Method
Roll Width		48 in.	
Roll Length		250 ft.	
Weight Per Square		1.8 lbs	
Nominal Thickness		7 Mils	
Water Transmission		Pass	ASTM D-4869
Tensile Strength			ASTM D-5034
	MD	57 lbs	
	CD	57 lbs	
Tear Strength			
	MD	36 lbs	
	CD	36 lbs	
Pliability		Pass	ASTM D-226

MEETS OR EXCEEDS REQUIREMENTS FOR ASTM D226 & D4869

STINGER-branded; 48" x 48".



ITEM #0342971

Co-branding available with 34" x 17" logo.



MK1039 800.746.5659 REV. 8/26/19 STINGERWORLD.COM



SYNTHETIC UNDERLAYMENT

- 25 year warranty.
- Made in the United States.
- Grey spunbond non-woven fabric walking surface
- Slip resistant back surface for added installation safety.
- 100% synthetic woven roof underlayment.
- Light only 18lbs per roll.
- 10 squares per roll fewer rolls to carry on the roof.
- UV resistant can be left exposed for up to 6 months.
- Preprinted nailing pattern and overlap lines to speed installation.
- Approved and warrantied for use under metal roof coverings.
- Recommended installation with STINGER[®] cap tools and cap fasteners, available in collated StaplePac[®] and NailPac[®] or HandDrive cap nails.

*Back surface is color-matched to the walking surface





STINGER CAP SYSTEMS

RECOMMENDED **BEST PRACTICE** FOR SECURING SYNTHETIC UNDERLAYMENTS AND HOUSEWRAP.

25 YEAR WARRANTY

MK1039 REV. 8/26/19